

# Ecoplát Plus

Turntable stretch wrapper



1ST SERVICE  
FREE



ROBOPAC

## KEY FEATURES

- Automatic pallet height detection by photocell
- Programmable wrapping cycles with memory recall
- USB port for software updates and data download
- IP54 rated - dust and water ingress protection
- Front and rear forklifting as standard
- R-Connect Industry 4.0 monitoring available

## HPS AFTER-SALE SUPPORT

UK engineer installation and operator training on handover. First annual service (labour) included with every machine we supply.

## ECOPLAT PLUS (BASE)

## ECOPLAT PLUS FRD

### TECHNICAL SPECIFICATIONS

#### TURNTABLE

Diameter (std)	1500mm
Diameter (opt)	1650mm
Max load - std	1200kg
Max load - opt	2000kg
Rotation speed	4-10 rpm

#### CARRIAGE

Type	Adjustable mechanical brake
Up/down speed	1.4-4 m/min
Film pre-stretch	Not fitted (Base model)

#### PALLET & FILM

Max pallet (L x W) std	800 x 1200mm
Max pallet (L x W) opt	1000 x 1200mm
Max product height	2200mm (std) / 2400mm (opt)
Film thickness range	17-35 um
Max reel (H x dia.)	500 x 300mm / max 20kg

#### POWER

Supply	230V 1Ph +/-10% / 50-60Hz
Installed power	1.2 kW
Protection rating	IP54

## ECOPLAT PLUS FRD - WHAT CHANGES

The FRD replaces the manual brake carriage with an electromagnetic brake unit for consistent film tension across varying load shapes. Adds a 3.5" LED panel with JOG parameter selector and 6 programmable cycles. Standard turntable also moves to 2000kg capacity. All other dimensions and power specs are identical.

HAYES PACKAGING SERVICE LTD

01707 819119 | sales@hayespackaging.co.uk

Specifications sourced from Robopac technical data. HPS reserves the right to verify individual machine configuration on enquiry.