

Minimum standards required to achieve accreditation

Ultrasonic Obstacle Detection

SS-4000W Sidescan® sensor system

4 sensor system increases safety when turning or low speed manoeuvring.



Warning Alarm

SS-BC-08 Speaking alarm

Speaking alarm with side turn warning for cyclists/pedestrians. Activates on left turn indication and complements Sidescan sensor system.



TCO-47-01 Latched auto-reset alarm cut-out (dash mount button)

Press to silence alarm. Press again to re-enable. Ignition reset.

Camera Monitor Systems

VBV-750M Select range 5" Digital LCD Monitor



VBV-700C Select range Rear view camera



VBV-300C Select range compact, flush-mount left side view camera



Select series camera monitors are our best selling, mid-range systems that offer quality and features at a cost-effective price.



Ultimate recommended safety specification

Warning Alarm

bbs-tek, white sound alarms are the safest in the world due to their instant locatability and directional sound. The alarm is only heard in the danger zone, thus eliminating noise nuisance.



SA-BBS-97 bbs-tek® White sound® smart reversing alarm. 77-97 dB

Continually adjusts to 5-10 decibels above ambient so ideal in varying noise level environments and urban areas

TCO-47 Latched auto-reset alarm cut-out (dash mount button)

To silence the reverse alarm for 4 minutes



Camera Monitor Systems

VBV-300C Select range compact, flush-mount right side view camera



Ultrasonic Obstacle Detection

FS-4000W Frontscan® sensor system

4 sensor system improves safety when manoeuvring at low speed.



Online at www.origingps.co.uk Call on 0141 353 9595

Safety recommendations for typical vehicle type. Selected products may change to suit different applications. Please see catalogue for individual specifications and full range of complementary safety solutions.