

FORS Compliance

Minimum standards required to achieve silver accreditation



Ultrasonic Obstacle Detection

SS-4000W Sidescan® sensor system

4 sensor system increases safety when turning or low speed manoeuvring.



Warning Alarm

SS-BC-08 Speaking alarm

Speaking alarm with side turn warning for cyclists/pedestrians. Activates on left turn indication and complements Sidescan sensor system.



SA-BBS-97 bbs-tek® White sound® smart reversing alarm. 77-97 dB

Continually adjusts to 5-10 decibels above ambient so ideal in varying noise level environments and urban areas.



Camera Monitor Systems

VBV-750M Select range 5" Digital LCD Monitor



VBV-700C Select range Rear view camera



VBV-300C Select range compact, flush-mount left side view camera

Select series camera monitors are our best selling, mid-range systems that offer quality and features at a cost-effective price.



Ultimate recommended safety specification



Warning Alarm

Cut Out Switch for Speaking Alarm (SS-BC-08)

TCO-47-01 Latched auto-reset alarm cut-out (dash mount button) Press to silence alarm. Press again to re-enable. Ignition reset.

Cut Out Switch for Reversing Alarm (SA-BBS-97)

TCO-47 Latched auto-reset alarm cut-out (dash mount button) To silence the reverse alarm for 4 minutes



Digital Recording

MDR-404-500

Mobile digital recorder with 500GB hard disk. Records footage from up to four cameras. All channels can be viewed on the monitor in the cab, aiding all round visibility for the driver.



Camera Monitor Systems

VBV-300C Select range compact, flush-mount right side view camera



Online at www.origingps.co.uk Call on 0141 353 9595

Safety recommendations for typical vehicle type. Selected products may change to suit different applications. Please see catalogue for individual specifications and full range of complementary safety solutions.