



TITLE		<p>NOTE: Purewater sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.</p>	<p>DESCRIPTION:</p> <p>PW.5x2x1.TIF Sectional cold water storage tank c/w raised float valve housing to provide an AB Air gap.</p>	DATE	VERSION	NOTES
DRAWN BY				24/01/2023	A	FIRST ISSUE
CUSTOMER						

<p>DATE</p> <p>VERSION</p> <p>NOTES</p>		<p>TANK SPECIFICATION :</p> <p>INTERNAL DIMENSIONS 5150 x 2150 x 1150mm</p> <p>EXTERNAL DIMENSIONS 5224 x 2224 x 1710mm</p> <p>NOM. CAPACITY 12,733 Litres</p> <p>INSULATION THICKNESS 38mm</p> <p>MATERIAL Hot press moulded GRP</p>		
<p>TITLE</p> <p>PW.5x2x1.TIF.AB</p>				SCALE:1:50
<p>DRAWN BY</p> <p>N.Amechi</p> <p>DATE</p> <p>30/01/2023</p>				SHEET 1 OF 1

<p>DESCRIPTION:</p> <p>PW.5x2x1.TIF Sectional cold water storage tank c/w raised float valve housing to provide an AB Air gap.</p>		<p>ALL DIMENSIONS IN MM - DO NOT SCALE</p>	
--	--	--	--

<p>INTERNAL DIMENSIONS</p> <p>5150 x 2150 x 1150mm</p>	
<p>EXTERNAL DIMENSIONS</p> <p>5224 x 2224 x 1710mm</p>	
<p>NOM. CAPACITY</p> <p>12,733 Litres</p>	
<p>INSULATION THICKNESS</p> <p>38mm</p>	
<p>MATERIAL</p> <p>Hot press moulded GRP</p>	

SCALE:1:50	SHEET 1 OF 1