



TITLE		<p>NOTE: Purewater sectional tanks must be fully supported on a flat, level & continuous foundation which provides structural support to the tank when full to maximum capacity. It is essential that the installer and/or user refers to the conditions of the installation document prior to the installation of the tank. Under no circumstances should any part of the tank structure be used to provide support to pipework and/or any ancillary items.</p>	<p>DESCRIPTION:</p> <p>PW.2x1.5x1.5.TIF Sectional cold water storage tank c/w raised float valve housing to provide an AB Air gap.</p>	DATE	VERSION	NOTES
PW.2x1.5x1.5.TIF.AB				25/01/2023	A	FIRST ISSUE
DRAWN BY	DATE					
N.Amechi	30/01/2023					
CUSTOMER		ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	A4	ALL DIMENSIONS IN MM - DO NOT SCALE		

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	2150 x 1650 x 1650mm
EXTERNAL DIMENSIONS	2224 x 1724 x 2210mm
NOM. CAPACITY	5,853 Litres
INSULATION THICKNESS	38mm
MATERIAL	Hot press moulded GRP

SCALE:1:40	SHEET 1 OF 1