

# Technical Report

Title: Impact testing of Barracuda Brick Slip System (Un-Mortared)

Report No: N950-24-18684



# Technical Report

**Title:** Impact Testing of Barracuda Brick Slip System (Un-Mortared).

**Customer:** James & Taylor Ltd,  
Sixty-Two, Barwell Business Park,  
Leatherhead Road, Chessington, Surrey KT9 2NY.

**Issue date:** 4 March 2024

**VTC job no.:** TR0220-3WK2

**Author(s):** S. Bahera – Assistant Engineer



**Checked by:** N. McDonald – Manager



**Authorised by:** S. R. Moxon – Operations Director



**Distribution:** 1 copy to James & Taylor  
(confidential) 1 copy to project file

This report and the results shown and any recommendations or advice made herein is based upon the information, drawings, samples and tests referred to in the report. Where this report relates to a test for which VINCI Technology Centre UK Limited is UKAS accredited, the opinions and interpretations expressed herein are outside the scope of the UKAS accreditation. We confirm that we have exercised all reasonable skill and care in the preparation of this report within the terms of this commission with the client. This approach takes into account the level of resources, manpower, testing and investigations assigned to it as part of the client agreement. We disclaim any responsibility to the client and other parties in respect of any matters outside the scope of our instruction. This report is confidential and privileged to the client, his professional advisers and VINCI Technology Centre UK Limited and we do not accept any responsibility of any nature to third parties to whom the report, or any part thereof, is made known. No such third party may place reliance upon this report. Unless specifically assigned or transferred within the terms of the agreement, we assert and retain all copyright, and other Intellectual Property Rights, in and over the report and its contents.



**VINCI Technology Centre UK Limited,  
Stanbridge Road, Leighton Buzzard, Bedfordshire, LU7 4QH**

Registered Office, Watford. Registered No. 05640885 England.

**Tel.** 0333 5669000  
**email** info@technology-centre.co.uk  
**web** www.technology-centre.co.uk

© Technology Centre

## CONTENTS

1	INTRODUCTION.....	4
2	SUMMARY AND CLASSIFICATION OF TEST RESULTS .....	5
3	IMPACT CLASSES .....	6
4	DESCRIPTION OF TEST SAMPLE.....	7
5	TEST EQUIPMENT .....	10
6	TEST PROCEDURE .....	11
7	TEST RESULTS .....	12
8	APPENDIX - DRAWINGS .....	26

## 1 INTRODUCTION

This certificate of test describes impact tests carried out at the request of James & Taylor Ltd. on 12<sup>th</sup> September 2023 at VINCI Technology Centre, Leighton Buzzard.

The test was carried out in accordance with CWCT TN75/76.

The test was witnessed by:

John Champion - James & Taylor Ltd.

This test report relates only to the actual sample as tested and described herein.

The results are valid only for sample(s) tested and the conditions under which the tests were conducted.

The long-term durability of the façade system is not assessed by these test methods.

VINCI Technology Centre UK Limited is accredited to ISO/IEC 17025:2017 by the United Kingdom Accreditation Service as UKAS Testing Laboratory No. 0057 for a schedule of tests. Tests listed above and marked with an asterisk are not on our schedule.

VINCI Technology Centre UK Limited is Approved Body No. 1766.

VINCI Technology Centre UK Limited is certified by BSI for:

- ISO 9001 Quality Management System,
- ISO 14001 Environmental Management System,
- ISO 45001 Occupational Health and Safety Management System.

## 2 SUMMARY AND CLASSIFICATION OF TEST RESULTS

Impact testing has been carried out for safety impacts only, serviceability impacts have not been carried out.

### Soft body impacts

500 J
Safety
Negligible risk

### Hard body impacts

10 J
Safety
Low Risk

### 3 IMPACT CLASSES

**Note:** Tables 1 is taken from CWCT TN76.

**Table 1 - Classes for safety performance**

Class	Explanation/examples
Negligible risk	No material dislodged during test, and No damage likely to lead to materials falling subsequent to test, and No sharp edges produced that would be likely to cause severe injury to a person during impact, and Cladding not penetrated by impactor.
Low risk	Maximum mass of falling particle 50 g, and Maximum mass of particle that may fall subsequent to impact 50 g, and No sharp edges produced that would be likely to cause severe injury during impact.
Moderate risk	Maximum mass of falling particle less than 500 g, and Maximum mass of particle that may fall subsequent to impact less than 500 g, and Cladding not penetrated by impact, and No sharp edges produced that would be likely to cause severe injury during impact.
High risk	Maximum mass of falling particle greater than 500 g, or Cladding penetrated by impact, or Sharp edges produced that would be likely to cause severe injury during impact.

## 4 DESCRIPTION OF TEST SAMPLE

The sample was mounted to a solid steel frame which was fixed to a concrete slab as shown in the photograph below.

PHOTO IMG-5655



TEST SAMPLE

PHOTO IMG-5358



SUPPORT BRACKET

PHOTO IMG\_5352



CLOSE UP OF BRICK SLIPS

## 5 TEST EQUIPMENT

The soft body impactor comprised a canvas spherical/conical bag 400 mm in diameter filled with 3 mm diameter glass spheres with a total mass of 50 kg suspended from a cord at least 3 m long.

The hard body impactor was solid steel ball of 62.5 mm diameter and mass of 1.0 kg.

## 6 TEST PROCEDURE

### 6.1 SOFT BODY

The impactor almost touched the face of the sample when at rest. It was swung in a pendular movement to hit the sample normal to its face.

The test was performed at the locations shown in Figure 1.

The impact energies were 500 J for safety.

### 6.2 HARD BODY

The impactor almost touched the face of the sample when at rest. It was swung in a pendular movement to hit the sample normal to its face.

The test was performed at the locations shown in Figure 2.


The impact energies were 10 J.

## 7 TEST RESULTS

**Test Date:** 14<sup>th</sup> September 2023

Ambient temperature = 20 °C

FIGURE 1




SOFT BODY IMPACT LOCATIONS

TABLE 3  
SOFT BODY IMPACT TEST RESULTS

Location	Impact energy (J)	Observations	Classification
1	500	No damage observed	Negligible risk
2	500	No damage observed	Negligible risk
3	500	No damage observed	Negligible risk
4	500	No damage observed	Negligible risk
5	500	No damage observed	Negligible risk
6	500	No damage observed	Negligible risk
7	500	No damage observed	Negligible risk
8	500	No damage observed	Negligible risk
9	500	No damage observed	Negligible risk
10	500	No damage observed	Negligible risk
11	500	No damage observed	Negligible risk
12	500	No damage observed	Negligible risk
13	500	No damage observed	Negligible risk
14	500	No damage observed	Negligible risk
15	500	No damage observed	Negligible risk
16	500	No damage observed	Negligible risk
17	500	No damage observed	Negligible risk
18	500	No damage observed	Negligible risk

FIGURE 2



HARD BODY IMPACT LOCATIONS

TABLE 4  
HARD BODY IMPACT TEST RESULTS

Location	Impact energy (J)	Observations	Classification
1	10	Crack through full height of tile	Low risk
2	10	Crack through full height of tile	Low risk
3	10	Crack through full height of tile. Small chip to corner of brick	Low risk
4	10	Minor indent	Negligible risk
5	10	Crack through full height of tile	Low risk
6	10	Crack through full height of tile	Low risk
7	10	Crack through full height of tile	Low risk
8	10	Crack through full height of tile. Small chip to corner of brick (4 g)	Low risk
9	10	Crack through full height of tile	Low risk
10	10	Minor indent	Negligible risk
11	10	Crack through full height of tile	Low risk
12	10	Crack through full height of tile	Low risk
13	10	Crack through full height of tile	Low risk
14	10	Crack through full height of tile	Low risk
15	10	Crack through full height of tile	Low risk
16	10	Crack through full height of tile	Low risk
17	10	Crack through full height of tile. Small chip to corner of brick	Low risk
18	10	Crack through full height of tile. Small chip to corner of brick (4 g)	Low risk

PHOTO IMG\_9288



SOFT BODY IMPACTOR

PHOTO IMG\_9311



HARD BODY IMPACTOR

PHOTO IMG\_9310




IMPACT LOCATION 1

PHOTO IMG\_9312



IMPACT LOCATION 2

PHOTO IMG\_9314



IMPACT LOCATION 3

PHOTO IMG\_9316



IMPACT LOCATION 5

PHOTO IMG\_9319



IMPACT LOCATION 6

PHOTO 9321



IMPACT LOCATION 7

PHOTO IMG\_9323



IMPACT LOCATION 8

PHOTO IMG\_9325




IMPACT LOCATION 9

PHOTO IMG\_9329



IMPACT LOCATION 9

PHOTO IMG\_9331



IMPACT LOCATION 11

PHOTO IMG\_9336



IMPACT LOCATION 12

PHOTO IMG\_9338



IMPACT LOCATION 13

PHOTO IMG\_9340



IMPACT LOCATION 14

PHOTO IMG\_9342



IMPACT LOCATION 15

PHOTO IMG\_9344



IMPACT LOCATION 16

PHOTO IMG\_9349



IMPACT LOCATION 17

PHOTO IMG\_9354



IMPACT LOCATION 18

## 8 APPENDIX - DRAWINGS


The following 4 unnumbered pages are copies of James & Taylor Limited drawings numbered:

- BSS-TRB-GA-001
- BSS-TRB-GA-002
- BSS-TRB-GA-003
- BSS-TRA-T1

---

END OF REPORT

# TEST RIG TYPE A - TEST 1 [UNMORTARED BRICK PULL]



## GENERAL NOTES:

DO NOT SCALE FROM THIS DRAWING.

THIS DRAWING IS TO BE READ IN CONJUNCTION  
WITH ALL RELEVANT JAMES & TAYLOR,  
ARCHITECT'S AND ENGINEER'S DRAWINGS.

■ = BLOCKLEY WINDERMERE GREY SOLID

215mm LONG 'STANDARD' SLIPS = 135 No.

■ = WIENERBERGER STAFFORDSHIRE  
SMOOTH CREAM

215mm LONG 'STANDARD' SLIPS = 30 No.

165mm LONG 'STANDARD' SLIPS = 38 No.

52mm LONG 'STANDARD' SLIPS = 38 No.

215mm LONG SLIPS WITH 'TOP' REBATE = 15 No.

215mm LONG SLIPS WITH 'BOTTOM' REBATE = 15 No.

165mm LONG SLIPS WITH 'TOP' REBATE = 1 No.

165mm LONG SLIPS WITH 'BOTTOM' REBATE = 1 No.

52mm LONG SLIPS WITH 'TOP' REBATE = 1 No.

52mm LONG SLIPS WITH 'BOTTOM' REBATE = 1 No.

REVISIONS: DATE:  
CLIENT:

**JAMES & TAYLOR LTD**

PROJECT:  
**BRICK SLIP SYSTEM**

TITLE:  
**TEST RIG TYPE A - TEST 1  
UNMORTARED BRICK PULL**

DATE:  
04/12/2021

DRAWN BY: CHECKED BY:  
**JSC** **JSC**



SCALE: PLOT SIZE:  
1:16 A3

DRAWING NUMBER: REVISION:  
**BSS-TRA-T1**


PLOT DATE: December 5, 2021 5:38 PM  
© James & Taylor Ltd - 2009

TEST RIG TYPE B  
STEEL FRAMING (TO BE PROVIDED BY TECHNOLOGY CENTRE)

4400




203x203x46 UC




3010

GROUND LEVEL + 500mm



203x203x46 UC



GENERAL NOTES:

DO NOT SCALE FROM THIS DRAWING.

THIS DRAWING IS TO BE READ IN CONJUNCTION  
WITH ALL RELEVANT JAMES & TAYLOR,  
ARCHITECT'S AND ENGINEER'S DRAWINGS.

STEEL FRAMING REQUIREMENT

203x203x46 UC (AS DRAWN)

60x60x6 RSA (AS DRAWN)

REVISIONS: \_\_\_\_\_ DATE: \_\_\_\_\_

CLIENT: JAMES & TAYLOR LTD

PROJECT: BRICK SLIP SYSTEM

TITLE: TEST RIG TYPE B  
GENERAL ARRANGEMENT

DATE: 03/12/2021


DRAWN BY: JSC CHECKED BY: JSC

SCALE: 1:16 PLOT SIZE: A3

DRAWING NUMBER: BSS-TRB-GA-001 REVISION: \_\_\_\_\_

PLOT DATE: December 5, 2021 5:40 PM © James & Taylor Ltd - 2009

**TEST RIG TYPE B**  
**METSEC BACKING WALL; STUDWORK, BASE, AND HEAD TRACK SETTING OUT/CONFIGURATION**



GENERAL NOTES:

DO NOT SCALE FROM THIS DRAWING.

THIS DRAWING IS TO BE READ IN CONJUNCTION  
WITH ALL RELEVANT JAMES & TAYLOR,  
ARCHITECT'S AND ENGINEER'S DRAWINGS.


METSEC REQUIREMENT  
VERTICAL STUDS  
150M12-75 (THEORETICAL LENGTH 2987mm) = 7 No.

BASE TRACK  
154M12-40 (THEORETICAL LENGTH 3602mm) = 1 No.

HEAD TRACK  
154M16-70s (THEORETICAL LENGTH 3602mm) = 1 No.

REVISIONS: DATE:  
CLIENT: JAMES & TAYLOR LTD  
PROJECT: BRICK SLIP SYSTEM  
TITLE: TEST RIG TYPE B  
GENERAL ARRANGEMENT  
DATE: 03/12/2021  
DRAWN BY: JSC CHECKED BY: JSC  
SCALE: 1:16 PLOT SIZE: A3  
DRAWING NUMBER: BSS-TRB-GA-002 REVISION:  
PLOT DATE: December 5, 2021 5:42 PM © James & Taylor Ltd - 2009

TEST RIG TYPE B  
'HELPING HAND' BRACKET, VERTICAL SUB-STRUCTURE AND BARRACUDA RAIL SETTING OUT/CONFIGURATION



GENERAL NOTES:

DO NOT SCALE FROM THIS DRAWING.

THIS DRAWING IS TO BE READ IN CONJUNCTION  
WITH ALL RELEVANT JAMES & TAYLOR,  
ARCHITECT'S AND ENGINEER'S DRAWINGS.

BARRACUDA HORIZONTAL RAIL REQUIREMENT

BAR-R1-1800 = 78 No.  
BAR-R2-1800 = 2 No.  
BAR-R3-1800 = 2 No.

BARRACUDA VERTICAL RAIL REQUIREMENT

BAR-VL1-2990 = 6 No.  
BAR-VT1-2990 = 1 No.

'HELPING HAND' BRACKET REQUIREMENT  
Nvelope 90 (ADJUSTMENT RANGE 92mm TO 132mm)

VERTICAL LOAD BEARING HELPING HAND = 7 No.  
RESTRAIN HELPING HAND = 28 No.

REVISIONS: DATE:

CLIENT:  
**JAMES & TAYLOR LTD**

PROJECT:  
**BRICK SLIP SYSTEM**

TITLE:  
**TEST RIG TYPE B  
GENERAL ARRANGEMENT**

DATE:  
03/12/2021

DRAWN BY: CHECKED BY:  
**JSC** **JSC**

SCALE: PLOT SIZE:  
1:16 A3

DRAWING NUMBER: REVISION:  
**BSS-TRB-GA-003**

PLOT DATE: December 5, 2021 5:45 PM  
© James & Taylor Ltd - 2009



**VINCI Technology Centre UK Limited**

**Stanbridge Road**

**Leighton Buzzard**

**Bedfordshire**

**LU7 4QH**

**UK**

**0333 5669000**

**info@technology-centre.co.uk**

**www.technology-centre.co.uk**