



NOTES:
 DO NOT SCALE FROM DRAWING.
 DIMENSIONS ARE IN MILLIMETRES.

ALL NON-BARRACUDA SYSTEM COMPONENTS ARE INTENDED TO BE 'INDICATIVE' ONLY.

A 'MOVEMENT JOINT' IS SHOWN WITH A TYPICAL INDICATIVE WIDTH OF 15mm. THE ACTUAL JOINT WIDTH USED, MUST BE ADEQUATE TO ACCOMMODATE ALL BUILDING MOVEMENTS THAT MIGHT OCCUR AT THAT JOINT LOCATION.

THE 'MOVEMENT JOINT' IS USUALLY FILLED WITH A POLYETHYLENE BACKING ROD AND LOW MODULUS SILICONE SEALANT.

ANY LOCATIONS WHERE THE CAVITY IS 'BRIDGED', WHICH MIGHT ENCOURAGE WATER TO 'TRACK BACK' TO THE INNER SKIN [DRY SIDE] OF THE CAVITY SHOULD INCORPORATE A FLASHING THAT DRAINS THIS WATER TO THE EXTERNAL FACE OF THE BRICKWORK.

02	2nd ISSUE	JSC	19/05/2026
01	FIRST ISSUE	JSC	12/12/2022
REV:	REVISION DETAIL:	CHKD:	DATE:

Barracuda BRICK SLIP SUPPORT SYSTEM

TYPICAL DETAIL

TITLE:
 VERTICAL SECTION
 HORIZONTAL MOVEMENT
 JOINT/JUNCTION BETWEEN
 BRICK SLIP PANELS

DATE:
 12/12/2022

SCALE:
 1:1

DRAWING NUMBER:
TD-B-109

PLOT SIZE:
 A3

REVISION:
 02