

NOTES:  
 DO NOT SCALE FROM DRAWING.  
 DIMENSIONS ARE IN MILLIMETRES.

ALL NON-BARRACUDA SYSTEM COMPONENTS ARE INTENDED TO BE 'INDICATIVE' ONLY.

'COMPRESSIBLE JOINTS' ARE SHOWN WITH A TYPICAL INDICATIVE WIDTH OF 10mm. THE ACTUAL JOINT WIDTH USED, MUST BE ADEQUATE TO ACCOMMODATE ALL BUILDING MOVEMENTS THAT MIGHT OCCUR AT THAT JOINT LOCATION.

THE 'MOVEMENT JOINTS' ARE USUALLY FILLED WITH A POLYETHYLENE BACKING ROD AND LOW MODULUS SILICONE SEALANT.

ANY LOCATIONS WHERE THE CAVITY IS 'BRIDGED', WHICH MIGHT ENCOURAGE WATER TO 'TRACK BACK' TO THE INNER SKIN [DRY SIDE] OF THE CAVITY SHOULD INCORPORATE A FLASHING THAT DRAINS THIS WATER TO THE EXTERNAL FACE OF THE BRICKWORK.

03	3rd ISSUE	JSC	19/05/2026
02	MAX CANTILEVER DIMENSION REVISED	JSC	17/01/2026
01	FIRST ISSUE	JSC	12/12/2022
REV:	REVISION DETAIL:	CHKD:	DATE:

## Barracuda

### BRICK SLIP SUPPORT SYSTEM

#### TYPICAL DETAIL

TITLE:  
**PLAN**  
 [EXTERNAL 90 DEGREE CORNER WITH 'BIRDSBEAK' ALUMINIUM CORNER TRIM]

DATE:  
 12/12/2022

SCALE:  
 1:1

DRAWING NUMBER:  
**TD-B-116**



PLOT SIZE:  
 A3

REVISION:  
 03

