

NOTES:  
DO NOT SCALE FROM DRAWING.  
DIMENSIONS ARE IN MILLIMETRES.

ALL NON-BARRACUDA SYSTEM  
COMPONENTS ARE INTENDED TO BE  
'INDICATIVE' ONLY.

A 'MOVEMENT JOINT' IS SHOWN WITH  
A TYPICAL INDICATIVE WIDTH OF  
15mm. THE ACTUAL JOINT WIDTH  
USED, MUST BE ADEQUATE TO  
ACCOMMODATE ALL BUILDING  
MOVEMENTS THAT MIGHT OCCUR AT  
THAT JOINT LOCATION.

THE 'MOVEMENT JOINT' IS USUALLY  
FILLED WITH A POLYETHYLENE  
BACKING ROD AND LOW MODULUS  
SILICONE SEALANT.

ANY LOCATIONS WHERE THE CAVITY IS  
'BRIDGED', WHICH MIGHT ENCOURAGE  
WATER TO 'TRACK BACK' TO THE INNER  
SKIN [DRY SIDE] OF THE CAVITY  
SHOULD INCORPORATE A FLASHING  
THAT DRAINS THIS WATER TO THE  
EXTERNAL FACE OF THE BRICKWORK.

01	FIRST ISSUE	JSC	12/12/2022
REV:	REVISION DETAIL:	CHKD:	DATE:

# Barracuda

BRICK SLIP SUPPORT SYSTEM


## TYPICAL DETAIL

TITLE:  
PLAN  
[VERTICAL EDGE OF PANEL]

DATE:  
12/12/2022

SCALE:  
1:1

DRAWING NUMBER:  
TD-B-106

  
PLOT SIZE:  
A3  
REVISION:  
01

