

NOTES:
DO NOT SCALE FROM DRAWING.
DIMENSIONS ARE IN MILLIMETRES.

ALL NON-BARRACUDA SYSTEM
COMPONENTS ARE INTENDED TO BE
'INDICATIVE' ONLY.

A 'MOVEMENT JOINT' IS SHOWN WITH
A TYPICAL INDICATIVE WIDTH OF
15mm. THE ACTUAL JOINT WIDTH
USED, MUST BE ADEQUATE TO
ACCOMMODATE ALL BUILDING
MOVEMENTS THAT MIGHT OCCUR AT
THAT JOINT LOCATION.

THE 'MOVEMENT JOINT' IS USUALLY
FILLED WITH A POLYETHYLENE
BACKING ROD AND LOW MODULUS
SILICONE SEALANT.

ANY LOCATIONS WHERE THE CAVITY IS
'BRIDGED', WHICH MIGHT ENCOURAGE
WATER TO 'TRACK BACK' TO THE INNER
SKIN [DRY SIDE] OF THE CAVITY
SHOULD INCORPORATE A FLASHING
THAT DRAINS THIS WATER TO THE
EXTERNAL FACE OF THE BRICKWORK.

01	FIRST ISSUE	JSC	12/12/2022
REV:	REVISION DETAIL:	CHKD:	DATE:

Barracuda

BRICK SLIP SUPPORT SYSTEM

TYPICAL DETAIL

TITLE:
VERTICAL SECTION
HORIZONTAL MOVEMENT
JOINT/JUNCTION BETWEEN
BRICK SLIP PANELS

DATE:
12/12/2022

SCALE:
1:1

PLOT SIZE:
A3

DRAWING NUMBER:
TD-B-109

REVISION:
01

