



NOTES:
DO NOT SCALE FROM DRAWING.
DIMENSIONS ARE IN MILLIMETRES.

ALL NON-BARRACUDA SYSTEM COMPONENTS ARE INTENDED TO BE 'INDICATIVE' ONLY.

A 'MOVEMENT JOINT' IS SHOWN WITH A TYPICAL INDICATIVE WIDTH OF 15mm. THE ACTUAL JOINT WIDTH USED, MUST BE ADEQUATE TO ACCOMMODATE ALL BUILDING MOVEMENTS THAT MIGHT OCCUR AT THAT JOINT LOCATION.

THE 'MOVEMENT JOINT' IS USUALLY FILLED WITH A POLYETHYLENE BACKING ROD AND LOW MODULUS SILICONE SEALANT.

ANY LOCATIONS WHERE THE CAVITY IS 'BRIDGED', WHICH MIGHT ENCOURAGE WATER TO 'TRACK BACK' TO THE INNER SKIN [DRY SIDE] OF THE CAVITY SHOULD INCORPORATE A FLASHING THAT DRAINS THIS WATER TO THE EXTERNAL FACE OF THE BRICKWORK.

01 | FIRST ISSUE | JSC | 12/12/2022
REV: REVISION DETAIL: CHKD: DATE:

Barracuda

BRICK SLIP SUPPORT SYSTEM

TYPICAL DETAIL

TITLE:
PLAN
VERTICAL MOVEMENT
JOINT/JUNCTION BETWEEN
BRICK SLIP PANELS

DATE:
12/12/2022



SCALE:
1:1

PLOT SIZE:

A3

DRAWING NUMBER:
TD-B-110

REVISION:

01