



NOTES:  
 DO NOT SCALE FROM DRAWING.  
 DIMENSIONS ARE IN MILLIMETRES.

ALL NON-BARRACUDA SYSTEM COMPONENTS ARE INTENDED TO BE 'INDICATIVE' ONLY.

A 'COMPRESSIBLE JOINT' IS SHOWN WITH A TYPICAL INDICATIVE WIDTH OF 10mm. THE ACTUAL JOINT WIDTH USED, MUST BE ADEQUATE TO ACCOMMODATE ALL BUILDING MOVEMENTS THAT MIGHT OCCUR AT THAT JOINT LOCATION.

THE 'MOVEMENT JOINT' IS USUALLY FILLED WITH A POLYETHYLENE BACKING ROD AND LOW MODULUS SILICONE SEALANT.

ANY LOCATIONS WHERE THE CAVITY IS 'BRIDGED', WHICH MIGHT ENCOURAGE WATER TO 'TRACK BACK' TO THE INNER SKIN [DRY SIDE] OF THE CAVITY SHOULD INCORPORATE A FLASHING THAT DRAINS THIS WATER TO THE EXTERNAL FACE OF THE BRICKWORK.

01 | FIRST ISSUE | JSC | 12/12/2022  
 REV: REVISION DETAIL: CHKD: DATE:

## Barracuda

### BRICK SLIP SUPPORT SYSTEM

#### TYPICAL DETAIL

TITLE:  
**PLAN**  
**WINDOW JAMB [BRICK REVEAL]**

DATE:  
**12/12/2022**

SCALE:  
**1:1**

PLOT SIZE:  
**A3**

DRAWING NUMBER:  
**TD-B-115**

REVISION:  
**01**