



NOTES:  
DO NOT SCALE FROM DRAWING.  
DIMENSIONS ARE IN MILLIMETRES.

ALL NON-BARRACUDA SYSTEM  
COMPONENTS ARE INTENDED TO BE  
'INDICATIVE' ONLY.

A 'COMPRESSIBLE JOINT' IS SHOWN  
WITH A TYPICAL INDICATIVE WIDTH  
OF 10mm. THE ACTUAL JOINT WIDTH  
USED, MUST BE ADEQUATE TO  
ACCOMMODATE ALL BUILDING  
MOVEMENTS THAT MIGHT OCCUR AT  
THAT JOINT LOCATION.

DEPENDENT UPON THE BRICK TYPE;  
FROGGED OR WITH CORE HOLES  
ETC. THE BRICK COURSE JUST  
BELOW THE BARRACUDA SYSTEM  
MAY NEED TO HAVE A REARWARD  
SLOPING CUT TO ENSURE THAT  
WATER DOES NOT COLLECT ON ITS  
UPPER SURFACE.

ANY LOCATIONS WHERE THE CAVITY IS  
'BRIDGED', WHICH MIGHT ENCOURAGE  
WATER TO 'TRACK BACK' TO THE INNER  
SKIN [DRY SIDE] OF THE CAVITY  
SHOULD INCORPORATE A FLASHING  
THAT DRAINS THIS WATER TO THE  
EXTERNAL FACE OF THE BRICKWORK.

01 | FIRST ISSUE | JSC | 12/12/2022  
REV: REVISION DETAIL: CHKD: DATE:

## Barracuda

### BRICK SLIP SUPPORT SYSTEM

#### TYPICAL DETAIL

TITLE:  
VERTICAL SECTION  
BASE DETAIL  
HORIZONTAL 'JUNCTION' WITH  
STANDARD BRICKWORK

DATE:  
12/12/2022

SCALE:  
1:1

PLOT SIZE:  
A3

DRAWING NUMBER:  
TD-B-118

REVISION:  
01