

ICOM

IC-M330GE

VHF Transceiver with GPS Receiver

SMALL IS COOL!

Top Performance Ultra-compact VHF



- Intuitive user interface
- Easy-to-read full dot-matrix display
- Improved speaker design delivers dynamic, clear audio
- Built-in GPS receiver and external GPS antenna
- Ultra-compact body (WxHxD : 156.5 x 66.5 x 110.1mm)
- Easily fitted where space is a premium!

• Ultra Compact Body, Flexible Installation

The compact IC-M330GE measures only 156.5 (W) x 66.5 (H) x 110.1 (D) mm making it ideal for a cockpit where space is limited.

• Intuitive User Interface

A combination of the directional keypad and soft keys provides simple, smooth operation. Most used functions are assigned to soft keys for quick one push function access.

• New Speaker Delivers Dynamic, Clear Audio

A newly designed speaker delivers distortion-free clear audio even at full volume. It provides dynamic and clear audio over a wide bass and treble range.

• Class-Leading Receiver Performance

The IC-M330GE's receiver provides reliable communication in RF busy environment like a marina. (Selectivity and IMD: more than 70 dB).

• Built-in Class D DSC

The radio monitors CH 70 continuously, even while you are receiving another channel. DSC functions include distress, individual, group, all ships, urgency, safety, position request/report, polling request and DSC test calls.

• Built in GPS Receiver and External GPS Antenna

The GPS receiver provides your location, bearing and speed by using information from GPS, GLONASS and SBAS. The acquired position information can be used for DSC calls.

An external GPS antenna is supplied to maximise coverage.

*IC-M330GE is the first ICOM fixed marine VHF radio to comply with the latest maritime ITU standard 'ITU-R M493-14'. This standard, in essence, requires an external GPS antenna, ITU-R M493-14 will be compulsory from November 2018. All maritime Class-D fixed radios from all manufacturers will need to comply after this date.



Supplied GPS antenna

• And more...

- IPX7 waterproof (1 metre depth of water for 30 minutes).
- AquaQuake™ prevents audio degradation from a water-logged speaker.
- Common NMEA interface for external GPS/NAV connection.
- MA-500TR Class B AIS transponder compatible.
- Tag scan and favourite channel functions.
- Dual/tri-watch function for monitoring CH16 and/or call channel.
- Priority scan function.
- Display and keypad backlighting.
- External speaker connection.
- 3-digit or 4-digit channel display selectable.

Ultra-compact!
35%



smaller than previous IC-M323G model!

OPTIONS



HM-235B/W

HAND MICROPHONE
Same as supplied.

SPECIFICATIONS

GENERAL		
Frequency range	Tx Rx CH70	156.000–162.000 MHz 156.000–163.425 MHz 156.525 MHz
Usable channels		INT, USA* channels * Available depending on version
Type of emission		16K0G3E (FM), 16K0G2B (DSC)
Power supply requirement		13.8 V DC nominal (10.8–15.6 V DC)
Current drain		
Tx	25 W output	5 A
Rx	Max. audio	1 A
Operating temperature range		–20°C to +60°C
Antenna impedance		50 Ω (SO-239)
Dimensions (W • H • D) (projections not included)		156.5 • 66.5 • 110.1 mm
Weight (approx.)		730 g
NMEA formats	In Out	RMC, GGA, GNS, GLL, VTG DSC, DSE, RMC, GSA, GSV
TRANSMITTER		
Output power		25 W, 1 W
Max. frequency deviation		±5.0 kHz
Frequency stability		Less than ±0.75 kHz
Spurious emissions		Less than 0.25 µW


RECEIVER		
Sensitivity	Main DSC	–5 dB• emf typ. (20 dB SINAD) –5 dB• emf typ. (1% BER)
Squelch sensitivity	Main	Less than –2 dBµ emf
Adjacent channel selectivity	Main	More than 70 dB
Spurious response	Main DSC	More than 73 dBµ emf (1% BER) More than 73 dBµ emf (1% BER)
Intermodulation	Main DSC	More than 70 dB More than 68 dBµ emf (1% BER)
Hum and noise		More than 40 dB
Audio output power (at 10% distortion, 4 Ω load)		More than 2 W

Measurements made in accordance with EN 301 025-2, -3. All stated specifications are subject to change without notice or obligation.


Applicable IP Rating

Ingress Protection Standard	
Water	IPX7 (Waterproof protection)

REAR PANEL VIEW



DIMENSIONS



ICOM-UK

Blacksole House, Altira Park, Herne Bay, Kent CT6 6GZ. UK.

Telephone: +44 (0)1227 741741. Fax: +44 (0)1227 741742. e-mail: info@icomuk.co.uk website: www.icomuk.co.uk



Radio Waves Communications UK Ltd
100 Unett Street North
Birmingham
B19 3JZ
Tel: 0333 303 4492
Email: sales@radiowavesuk.co.uk
Web: www.radiowavesuk.co.uk

Count on us!