



Longwrap

Technical Data Sheet

DESCRIPTION

Longwrap LD Mastic is a VOC Free, cold applied, wax based putty filled with expanded polystyrene beads that is designed to fill gaps and irregular contours prior to the application of Longwrap or Maflowrap tapes.

LD Mastic comes in small bricks that can be applied to the substrate and contoured with a gloved hand.

SUBSTRATE COMPATIBILITY Steel, Stainless Steel, Ductile Iron, Other Metals, FBE, PE, PP, Concrete

RECOMMENDED USE Ideal for mechanical couplings, nuts, bolts, bell and spigot joints, saddle tees, leak clamps and any area that a smoother more contoured coating surface is preferred prior to application of Longwrap or Maflowrap tapes.

PRIMER Longwrap Paste or B400 Primer are recommended to ensure maximum effectiveness of the system. The LD Mastic can be applied immediately following the primer application.

SURFACE PREPARATION SSPC SP-2 Hand Tool Cleaning, SSPC SP-3 Power Tool Cleaning or SSPC SP-6/ NACE No. 3 Commercial Blast Cleaning

SAFETY Refer to Material Safety Data Sheet: MSDS-LD-Mastic

APPLICATION Refer to Application Guidelines: AG-COLD-APPLIED-PET-LONGWRAP

TYPICAL DATA

Property	Metric	US Customary	Test Method
Color	Yellow	Yellow	
VOC Content	0 g/l	0 lb/gal	
Service Temperature Range	5 °C to 60 °C	40 °F to 140 °F	

ORDERING INFORMATION

Slab Size (nominal)	Slabs Per Case	Weight
45mm x 135mm x 500mm	6	2.5 kg per slab

The information contained here is provided for product selection purposes only and is not to be considered specification or performance data. Under no circumstance will the seller be liable for any loss, damage, expense or incidental or consequential damage of any kind arising in connection with the use or inability to use its product. Specific conditions of sale and Chase's limited warranty are set out in detail in Chase Corporation Terms and Conditions of Sale. Those Terms and Conditions are the only source that contain Chase's limited warranty and other terms and conditions.

Chase Protective Coatings Ltd
 Harbour Road,
 Rye, East Sussex, TN31 7TE, UK

Phone: +44(0)1797.223561
 Fax: +44(0)1797.224530
www.chasecorp.com

A BS EN ISO 9001:2008
 REGISTERED COMPANY

Chase Corporation
 295 University Avenue
 Westwood, MA 02090

Phone: 800-323-4182
 Fax: 781-332-0701
www.chasecorp.com

An ISO 9001:2008
 REGISTERED COMPANY