



## Dimensions

<b>Width</b>	436 mm
<b>Height</b>	551 mm
<b>Depth</b>	387 mm
<b>Flue Diameter</b>	127 mm
<b>Depth from back to centre of top flue</b>	82 mm
<b>Height to centre of rear flue</b>	448 mm
<b>Ideal log length / diameter</b>	300mm / 100mm

## Performance—Wood & Solid Fuel

	<b>Wood Fuel</b>	<b>Solid Fuel</b>
<b>Energy Efficiency Class</b>	A	E
<b>Nett Efficiency</b>	80.6 %	79.7 %
<b>Nominal Output</b>	4.9 kW	4.9 kW
<b>Output Range</b>	4.4 – 6.9 kW	
<b>Mean Co Emission (@13% O<sub>2</sub>)</b>	0.09 %	0.11 %
<b>DIN+ particulate</b>	22 Nmg/m <sup>3</sup>	33 Nmg/m <sup>3</sup>
<b>Mean NOx Emission (@13% O<sub>2</sub>)</b>	104 Nmg/m <sup>3</sup>	132 Nmg/m <sup>3</sup>
<b>Mean OGC Emission (@13% O<sub>2</sub>)</b>	67 Nmg/m <sup>3</sup>	44 Nmg/m <sup>3</sup>
<b>Flue Gas Mass Flow</b>	4.0 g/s	3.8 g/s
<b>Flue Gas Temperature</b>	265 °C	275°C
<b>Typical Fuel load for nominal rated output per hour (kWh/Kg)</b>	1.10(Seasoned hardwood)	0.75 (MSF Maxibrite)

## Product Fiche

<b>Supplier name</b>	Arada
<b>Product Code</b>	SOL5-S4
<b>Energy Efficiency Class (wood)</b>	A
<b>Direct Heat Output (wood)</b>	4.9 Kw
<b>Indirect Heat Output (wood)</b>	N/A
<b>Energy Efficiency Index (wood)</b>	105.1

**The useful energy efficiency at nominal heat output and at minimum load (wood)** 80.6 %

### Specific precautions that shall be taken when the local space heater is assembled, installed or maintained:

Product should be installed in accordance with local building regulations. Appliance will become very hot during use.

## Features

<b>Flexifuel</b>	No
<b>Stove body type</b>	Freestanding
<b>Ecodesign Ready</b>	Yes
<b>Suitable for smoke control areas</b>	Yes
<b>Suitable for direct air connection</b>	Yes *
<b>Suitable for non-combustible 12mm hearth</b>	Yes
<b>Weight gross (packed kg)</b>	68.5 Kg

## Minimum distance to combustibles

	<b>A</b>	<b>B</b>	<b>C</b>
<b>Rear</b>	750 mm	500 mm	350 mm
<b>Side</b>	550 mm	550 mm	550 mm
<b>Max hearth temp</b>	54 °C	54 °C	58 °C
A = Single Walled Flue, without Rear Heat Shield fitted			
B = Single Walled Flue, with Rear Heat Shield fitted			
C = Twin Walled Flue, with Rear Heat Shield fitted			

## Direct air spigot location

### When viewing the rear side of stove

<b>Spigot diameter</b>	125 mm
<b>Height from floor</b>	TBA mm
<b>Lateral position</b>	Centre
* Note: The optional direct air adaptor for this model is not room-sealed and should not be installed on a stove in an air-tight property	