

## Premseal Primer

Fast-drying primer for the preparation of surfaces

### Composition

Premseal Primer is comprised of a bitumen solution.

### Uses

Premseal Primer is used in conjunction with Premseal Waterproof Membrane in order to consolidate the substrate and ensure complete bond development.

### Characteristics

Premseal Primer:

- is easy to apply,
- enhances tape adhesion, and
- enhances corrosion protection of the system .

### Surface Preparation

Surfaces must be clean, dry and free from rust, scale and non-adherent coatings. Preferably, the area will be abrasive blast cleaned or well wire brushed.

### Application

See *Instructions for Use* for additional detail.  
Apply Premseal Primer evenly over the surface using a brush.

### Availability

Premseal Primer is available in 5 litre, 25 litre and 200 litre drums.

### Storage conditions

Store all components upright in original packaging in a cool and dry place. Keep away from heat, sparks and open flames.

### Waste material

Please do not discard waste material, including packaging, in the surrounding environment. Please follow all relevant legislation for disposal.

### Typical Properties

Specific Gravity	0.92
Solids Content	48% w/w
Flash Point	>39°C
Viscosity	500 cP
Surface Coverage	6-8 m <sup>2</sup> /Litre
WFT	90-110 microns
DFT	45-60 microns