

# Premseal Primer LT

Fast-drying primer for the preparation of surfaces

## Composition

Premseal Primer LT is comprised of bitumen and aromatic hydrocarbon solvents.

## Uses

Premseal Primer LT used in conjunction with Premseal 100 LT makes up the Premseal 100 LT Waterproofing Membrane System.

Premseal Primer LT is moisture tolerant allowing it to be used on green concrete or damp to touch substrates. It can be applied at low temperatures and is quick drying. Allowing early application reduces delays to the building programme, even in marginal weather conditions.

## Characteristics

Premseal Primer LT:

- is moisture tolerant,
- is easy to apply at low temperatures,
- enhances tape adhesion, and
- enhances corrosion protection of the system.

## Typical Properties

Specific Gravity	0.92
Solids Content	48% w/w
Surface Coverage	
On concrete	6-8 m <sup>2</sup> /Litre
On lightweight concrete	3-5 m <sup>2</sup> /Litre

## Application

See *Instructions for Use* for additional detail.  
Apply Premseal Primer LT evenly over the surface using a brush.

## Availability

Premseal Primer LT is available in 5 litre, 25 litre and 200 litre drums.

## Storage conditions

Store all components upright in original packaging in a cool and dry place. Keep away from heat, sparks and open flames.

## Waste material

Please do not discard waste material, including packaging, in the surrounding environment. Please follow all relevant legislation for disposal.