



40mm Encapsulated
RHS Steel Bracing

305

TITLE		<p>PW1220.INS.AG</p> <p>DRAWN BY C.MORRIS DATE 09/05/2023</p> <p>CUSTOMER CUSTOMER</p>
NOTE:		
<p>All Purewater tanks must be fully supported on a flat level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.</p>		
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED		A4

DESCRIPTION:	PW1220 one piece cold water storage tank suitable for AG/AF Air gap
ALL DIMENSIONS IN MM - DO NOT SCALE	

DATE	VERSION	NOTES
09/10/2017	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1000 x 1000 x 1220mm
EXTERNAL DIMENSIONS	1165 x 1165 x 1313mm
NOM. CAPACITY	1220 Litres
DRY WEIGHT	70 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	131006
MATERIAL	GRP



SCALE:1:20 SHEET 1 OF 1