



3 No 40mm Encapsulated
RHS Steel Bracings

TITLE PW1050.INS.AG	
DRAWN BY C.MORRIS	DATE 05/05/2023
CUSTOMER CUSTOMER	

NOTE: All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED

DESCRIPTION: PW1050 one piece cold water storage tank suitable for AG/AF Air gap
ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
22/10/2019	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1500 x 500 x 1400mm
EXTERNAL DIMENSIONS	1665 x 665 x 1477mm
NOM. CAPACITY	1050 Litres
DRY WEIGHT	82 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	131006
MATERIAL	GRP

purewater storage ltd

SCALE: 1:20 SHEET 1 OF 1