



TITLE		NOTE: All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.	
PW9000.INS.AG			
DRAWN BY	J. Ellison	DATE	24/05/2023
CUSTOMER	CUSTOMER	ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	

DESCRIPTION:	
PW9000 one piece cold water storage tank suitable for AG/AF Air gap	
A4	

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	3000 x 2000 x 1500mm
EXTERNAL DIMENSIONS	3192 x 2192 x 1593mm
NOM. CAPACITY	9000 Litres
DRY WEIGHT	405 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	131006
MATERIAL	GRP

DATE	VERSION	NOTES
06/11/2017	A	FIRST ISSUE

SCALE: 1:30		SHEET 1 OF 1	
-------------	--	--------------	--

