

6

5

4

3

2

1



D

A technical line drawing of a double door unit. The unit consists of two rectangular panels. The left panel is smaller and positioned inside the right panel. Both panels have a double-line border. The overall width of the unit is indicated by a dimension line at the bottom labeled '2202'. To the left of the unit, a vertical dimension line on the left edge is labeled '1202', indicating the height of the left panel. The drawing also shows several circular punch holes along the outer edges of both panels.

C

A technical line drawing of a double-decker bus. The bus is shown from a front-three-quarter perspective, highlighting its two levels. A vertical dimension line on the left side of the bus indicates its height. The text '1093' is written vertically along this dimension line, indicating the bus's height in millimeters.

A

PW2000.INS-2.AG

NOTE

All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

DESCRIPTION

PW2000-2 piece cold water storage tank
suitable for AG/AF Air gap

DATE	VERSION	NOTES
10/10/2017	A	FIRST ISSUE

TANK SPECIFICATION :

purewater
storage ltd.

Page 1 of 1

6

5

4

3

2

1