

6

5

△

3

1

1



D

A technical drawing of a rectangular frame. The outer dimensions are indicated by a dimension line on the left side, labeled '1410', and a dimension line at the bottom labeled '2610'. The frame features a central rectangular cutout. There are several circular punch holes along the outer and inner edges of the frame. The drawing is composed of black lines on a white background.

C

The diagram illustrates a structure composed of four distinct horizontal layers. The top layer is a thin, dark horizontal line. Below it is a thick, dark horizontal line. The third layer is a thin, dark horizontal line. The bottom layer is a thick, dark horizontal line. A vertical dimension line on the left side of the diagram is labeled '1163', indicating the total height of the structure. The top of the structure features a series of small, dark, horizontal tick marks.

A

PW3185.INS-2.AG

NOTE:

All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

DESCRIPTION

PW3185-2 piece cold water storage tank
suitable for AG/AF Air gap

DATE	VERSION	NOTES
2024-01-01	1.0	Initial version

TANK SPECIFICATION

pure water
storage ltd.

SHEET 1 OF 1

6

5

△

3

1

1