



TITLE		<small>NOTE:</small> All Purewater tanks must be fully supported on a flat level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.	DESCRIPTION: PW160-2 piece cold water storage tank suitable for AG/AF Air gap	DATE	VERSION	NOTES
PW160.INS-2.AG				08/09/2017	A	FIRST ISSUE
DRAWN BY	C.MORRIS			DATE	05/12/2017	
CUSTOMER	CUSTOMER	ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED		A4		ALL DIMENSIONS IN MM - DO NOT SCALE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	760 x 460 x 460mm
EXTERNAL DIMENSIONS	950 x 655 x 499mm
NOM. CAPACITY	160 Litres
DRY WEIGHT	13 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	131006
MATERIAL	GRP

		SCALE:1:10	SHEET 1 OF 1
--	--	------------	--------------