







TITLE	
PW338.INS-2 (AG)	
DRAWN BY	J. Ellison
DATE	16/12/2021
CUSTOMER	CUSTOMER

NOTE:	
All Purewater tanks must be fully supported on a flat level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.	
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	A4

DESCRIPTION:	
PW338-2 piece cold water storage tank suitable for AG/AF Air gap	
ALL DIMENSIONS IN MM - DO NOT SCALE	

DATE	VERSION	NOTES
16/12/2021	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	610 x 610 x 910mm
EXTERNAL DIMENSIONS	805 x 805 x 949mm
NOM. CAPACITY	338 Litres
DRY WEIGHT	25 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	131006
MATERIAL	GRP

purewater storage ltd	
SCALE:1:20	SHEET 1 OF 1