



| TITLE | NOTE: All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. | DESCRIPTION: PW375.OPEN Cold water storage tank | TANK SPECIFICATION : | | |
|------------------------|--|--|-------------------------------------|---|----------------------|
| | | | DATE 16/12/2021 | VERSION A | NOTES FIRST ISSUE |
| DRAWN BY J. Ellison | DATE 16/12/2021 | | | | |
| CUSTOMER CUSTOMER | ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED | A4 | ALL DIMENSIONS IN MM - DO NOT SCALE | | |
| | | | | MATERIAL GRP | SCALE:1:20 |
| | | | | INTERNAL DIMENSIONS 500 x 500 x 1500mm | SHEET 1 OF 1 |
| | | | | EXTERNAL DIMENSIONS 625 x 625 x 1505mm | |
| | | | | NOM. CAPACITY 375 Litres | |
| | | | | DRY WEIGHT 30 KG | |
| | | | | INSULATION THICKNESS NONE | |