



<b>TITLE</b> PW2250.OPEN		<b>NOTE:</b> All Purewater tanks must be fully supported on a flat level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items.		<b>DESCRIPTION:</b> PW2250.OPEN Cold water storage tank		<table border="1"> <thead> <tr> <th>DATE</th> <th>VERSION</th> <th>NOTES</th> </tr> </thead> <tbody> <tr> <td>16/12/2021</td> <td>A</td> <td>FIRST ISSUE</td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>		DATE	VERSION	NOTES	16/12/2021	A	FIRST ISSUE																			<b>TANK SPECIFICATION :</b>			
DATE	VERSION	NOTES																																	
16/12/2021	A	FIRST ISSUE																																	
<b>DRAWN BY</b> J. Ellison <b>DATE</b> 16/12/2021		<b>CUSTOMER</b> CUSTOMER		<b>A4</b>		ALL DIMENSIONS IN MM    DO NOT SCALE		<table border="1"> <tbody> <tr> <td>INTERNAL DIMENSIONS</td> <td>1500 x 1000 x 1500mm</td> </tr> <tr> <td>EXTERNAL DIMENSIONS</td> <td>1625 x 1125 x 1505mm</td> </tr> <tr> <td>NOM. CAPACITY</td> <td>2250 Litres</td> </tr> <tr> <td>DRY WEIGHT</td> <td>190 KG</td> </tr> <tr> <td>INSULATION THICKNESS</td> <td>NONE</td> </tr> <tr> <td>MATERIAL</td> <td>GRP</td> </tr> </tbody> </table>		INTERNAL DIMENSIONS	1500 x 1000 x 1500mm	EXTERNAL DIMENSIONS	1625 x 1125 x 1505mm	NOM. CAPACITY	2250 Litres	DRY WEIGHT	190 KG	INSULATION THICKNESS	NONE	MATERIAL	GRP	SCALE:1:25     SHEET 1 OF 1													
INTERNAL DIMENSIONS	1500 x 1000 x 1500mm																																		
EXTERNAL DIMENSIONS	1625 x 1125 x 1505mm																																		
NOM. CAPACITY	2250 Litres																																		
DRY WEIGHT	190 KG																																		
INSULATION THICKNESS	NONE																																		
MATERIAL	GRP																																		