



3 No 40mm Encapsulated  
RHS Steel Bracing

TITLE  
**PW1050.INS.AB.4**

DRAWN BY  
C.MORRIS

DATE  
05/05/2023

CUSTOMER  
CUSTOMER

**NOTE:**  
All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

ALL DIMENSIONS +/- 5mm  
UNLESS OTHERWISE STATED

DESCRIPTION:  
PW1050 one piece cold water storage tank c/w raised float valve housing to provide an AB Air gap

A4

ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
23/10/2020	A	FIRST ISSUE

**TANK SPECIFICATION :**

INTERNAL DIMENSIONS	1500 x 500 x 1400mm
EXTERNAL DIMENSIONS	1665 x 665 x 1725mm
NOM. CAPACITY	1050 Litres
DRY WEIGHT	85 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	131006
MATERIAL	GRP

SCALE:1:20

SHEET 1 OF 1