


40mm Encapsulated
RHS Steel Bracing



TITLE	
PW1818.INS.AB.4	
DRAWN BY	DATE
J. Ellison	15/05/2023
CUSTOMER	
CUSTOMER	

NOTE:
All Purewater tanks must be fully supported on a flat level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED

DESCRIPTION:
PW1818 one piece cold water storage tank c/w raised float valve housing to provide an AB Air gap
ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
02/10/2017	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1220 x 1220 x 1220mm
EXTERNAL DIMENSIONS	1390 x 1390 x 1545mm
NOM. CAPACITY	1818 Litres
DRY WEIGHT	125 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	131006
MATERIAL	GRP



SCALE:1:30 SHEET 1 OF 1