


25mm Encapsulated
RHS Steel Bracing



TITLE PW251.INS.AB	
DRAWN BY C.MORRIS	DATE 03/05/2023
CUSTOMER CUSTOMER	

NOTE: All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED

DESCRIPTION: PW251 one piece cold water storage tank c/w raised float valve housing to provide an AB Air gap
A4
ALL DIMENSIONS IN MM - DO NOT SCALE

DATE	VERSION	NOTES
05/10/2017	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	500 x 500 x 1000mm
EXTERNAL DIMENSIONS	675 x 675 x 1327mm
NOM. CAPACITY	250 Litres
DRY WEIGHT	20 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	131006
MATERIAL	GRP

purewater storage ltd

SCALE:1:20 SHEET 1 OF 1