



25mm Encapsulated Steel Bracing

TITLE		<p>PW338.INS.AB</p> <p>DRAWN BY C.MORRIS DATE 03/05/2023</p> <p>CUSTOMER CUSTOMER</p>
NOTE:		
<p>All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.</p>		
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED		A4

DESCRIPTION:		<p>PW338 cold water storage tank c/w raised float valve housing to provide an AB Air gap</p>
ALL DIMENSIONS IN MM - DO NOT SCALE		

DATE	VERSION	NOTES
07/10/2020	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	610 x 610 x 910mm
EXTERNAL DIMENSIONS	775 x 775 x 1250mm
NOM. CAPACITY	338 Litres
DRY WEIGHT	25 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	131006
MATERIAL	GRP



SCALE:1:20 SHEET 1 OF 1