



TITLE PW570.INS.AB.4		NOTE: All Purewater tanks must be fully supported on a flat level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.		DESCRIPTION: PW570 one piece cold water storage tank c/w raised float valve housing to provide an AB Air gap		<table border="1"> <thead> <tr> <th>DATE</th> <th>VERSION</th> <th>NOTES</th> </tr> </thead> <tbody> <tr> <td>18/09/2017</td> <td>A</td> <td>FIRST ISSUE</td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>		DATE	VERSION	NOTES	18/09/2017	A	FIRST ISSUE																									TANK SPECIFICATION :			
DATE	VERSION	NOTES																																							
18/09/2017	A	FIRST ISSUE																																							
DRAWN BY C.MORRIS DATE 04/05/2023		CUSTOMER CUSTOMER		A4		ALL DIMENSIONS IN MM - DO NOT SCALE		<table border="1"> <tbody> <tr> <td>INTERNAL DIMENSIONS</td> <td>990 x 760 x 760mm</td> </tr> <tr> <td>EXTERNAL DIMENSIONS</td> <td>1150 x 925 x 1085mm</td> </tr> <tr> <td>NOM. CAPACITY</td> <td>570 Litres</td> </tr> <tr> <td>DRY WEIGHT</td> <td>38 KG</td> </tr> <tr> <td>INSULATION THICKNESS</td> <td>25mm</td> </tr> <tr> <td>WRAS CERT. NUMBER</td> <td>131006</td> </tr> <tr> <td>MATERIAL</td> <td>GRP</td> </tr> </tbody> </table>		INTERNAL DIMENSIONS	990 x 760 x 760mm	EXTERNAL DIMENSIONS	1150 x 925 x 1085mm	NOM. CAPACITY	570 Litres	DRY WEIGHT	38 KG	INSULATION THICKNESS	25mm	WRAS CERT. NUMBER	131006	MATERIAL	GRP	SCALE:1:15 SHEET 1 OF 1																	
INTERNAL DIMENSIONS	990 x 760 x 760mm																																								
EXTERNAL DIMENSIONS	1150 x 925 x 1085mm																																								
NOM. CAPACITY	570 Litres																																								
DRY WEIGHT	38 KG																																								
INSULATION THICKNESS	25mm																																								
WRAS CERT. NUMBER	131006																																								
MATERIAL	GRP																																								