



TITLE		<p>NOTE: All Purewater tanks must be fully supported on a flat level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.</p>
DRAWN BY	DATE	
C.MORRIS	05/05/2023	
CUSTOMER	CUSTOMER	

DESCRIPTION:	
PW909 one piece cold water storage tank c/w raised float valve housing to provide an AB Air gap	
A4	

ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED		ALL DIMENSIONS IN MM - DO NOT SCALE	
--	--	-------------------------------------	--

DATE	VERSION	NOTES
19/09/2017	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	1168 x 890 x 890mm
EXTERNAL DIMENSIONS	1330 x 1050 x 1215mm
NOM. CAPACITY	909 Litres
DRY WEIGHT	50 KG
INSULATION THICKNESS	25mm
WRAS CERT. NUMBER	131006
MATERIAL	GRP



SCALE:1:20 SHEET 1 OF 1