



TITLE <b>PW2000-UN</b>		DATE 10/01/2022
DRAWN BY J. Ellison	CUSTOMER CUSTOMER	

**NOTE:**  
All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.

ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED

**DESCRIPTION:**  
PW2000-UN One piece cold water storage tank suitable for AG/AF Air gap

A4

ALL DIMENSIONS IN MM DO NOT SCALE

DATE	VERSION	NOTES
10/01/2022	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	2000 x 1000 x 1000mm
EXTERNAL DIMENSIONS	2202 x 1202 x 1093mm
NOM. CAPACITY	2000 Litres
DRY WEIGHT	148 KG
INSULATION THICKNESS	NONE
WRAS CERT. NUMBER	131006
MATERIAL	GRP

**purewater** storage ltd

SCALE:1:30 SHEET 1 OF 1