



TITLE		<p>NOTE: All Purewater tanks must be fully supported on a flat, level & continuous foundation providing structural support to the tank when full to maximum operating capacity. It is essential that the user refers to the conditions of installation document prior to the installation of the tank. Under no circumstances should the tank body be used to provide support to pipework and ancillary items. The tank lid is a structural part of the tank and must be in place and fitted correctly when water is contained within the tank.</p>
PW3001-UN		
DRAWN BY	DATE	
J. Ellison	10/01/2022	
CUSTOMER		
CUSTOMER		

DESCRIPTION:	
PW3001-UN One piece cold water storage tank suitable for AG/AF Air gap	
ALL DIMENSIONS +/- 5mm UNLESS OTHERWISE STATED	A4

DATE	VERSION	NOTES
10/01/2022	A	FIRST ISSUE

TANK SPECIFICATION :	
INTERNAL DIMENSIONS	2000 x 1000 x 1500mm
EXTERNAL DIMENSIONS	2202 x 1202 x 1588mm
NOM. CAPACITY	3000 Litres
DRY WEIGHT	195 KG
INSULATION THICKNESS	NONE
WRAS CERT. NUMBER	131006
MATERIAL	GRP

SCALE: 1:35 SHEET 1 OF 1